

COMMANDER SERIES EXTRA HEAVY-DUTY TOP FIRED GAS BROILER, CABINET BASE



Model FS-HB-1 shown with stainless steel doors







Design Certified by the American Gas Association Design Certified by the Canadian Gas Association Listed by the National Sanitation Foundation

Approved by	
Date:	

6 WEEK LEAD TIME.

SPECIFY TYPE OF GAS AND FINISH WHEN ORDERING. SPECIFY ALTITUDE WHEN ABOVE 2,000 FT.

BASIC MODEL:

FS-HB Top fired gas broiler, cabinet base

KEY FEATURES:

- Stainless steel front. Sides and top finished in black epoxy powder coat paint. 6" adjustable legs.
- ➤ 1¼" diameter front gas manifold.
- Rear gas connection 1¼".
- ➤ Four 25,000 BTU/hr. heavy-duty stainless steel radiant burners, 100,000 BTU/hr. total input.
- Pilot ignition system.
- Two infinite heat control valves.
- ➤ Floating grid rack assembly with positive positioning control handle. Two section cooking grid measures 25½" x 25½".
- Full width floating drip pan drains into a large capacity grease collector.
- ➤ 33"w x 23"d x 15½"h cabinet storage base.
- ➤ One year limited parts and labor warranty.

OPTIONAL FEATURES:

- 28"w x 20"d x 13"h finishing oven with manual heat control damper.
- > Four 20,000 BTU/hr. Miracle Ray infrared burners in place of radiant burners. 80,000 BTU/hr. total input.
- > Stainless steel doors for cabinet base.
- Stainless steel side(s).
- > Stainless steel top.
- > Stainless steel finishing back.
- Common stainless steel bullnose up to 108" wide. (Provide a drawing showing the position of each piece of equipment in the line-up with the order.)
- > Cap and cover manifold end(s). (No charge.)
- Leveling bolts in place of legs for curb installation.
- > Set of four 5" diameter casters, two locking.
- > Stainless steel dolly frame with casters, up to 96" wide.
- ➢ Rear gas connection ¾".

DESCRIPTION:

Heavy-duty top fired gas broiler on cabinet base, Wolf Model No. FS-HB. Stainless steel front. Sides and top finished in black epoxy powder coat paint. 6" adjustable legs. $1\frac{1}{4}$ " diameter front gas manifold. Four 25,000 BTU/hr. heavy-duty stainless steel radiant burners, 100,000 BTU/hr. total input. Pilot ignition system. Two infinite heat control valves. Floating grid rack assembly with positive positioning control handle. Two section cooking grid measures $25\frac{1}{2}$ " x $25\frac{1}{2}$ ". Full width floating drip pan drains into a large capacity grease collector. 33"w x 23"d x $15\frac{1}{2}$ "h cabinet storage base.

Exterior dimensions: 36"w x 38½"d x 63½"h on 6" adjustable legs.

WOLF RANGE COMPANY

Wolf Range Company, LLC
19600 S. Alameda St., Compton, CA 90221-6291
P.O. Box 7050, Compton, CA 90240-7050
(310) 637-3737 • FAX (310) 637-7931 • (800) 366-WOLF
Customer Service (888) 639-9653 • www.WOLFRANGE.com




Commander Series Extra Heavy-Duty Top Fired Gas Broiler, Cabinet Base

ACCESSORIES:

- Gas pressure regulator (specify size and type of gas).
- Flexible gas hose with quick disconnect and restraining device. Consult price book for available sizes.

CURB INSTALLATION Allow 3-1/2' front overhang 3-1/2'




Model FS-HB-1 (with Finishing Oven)

INSTALLATION REQUIREMENTS:

- In order for this equipment to operate as designed, an adequate gas supply (volume and pressure) must be delivered to the installation. Natural gas 5.0" W.C., propane gas 10.0" W.C.
- 2. A properly sized gas pressure regulator must be installed with this equipment.
- An adequate ventilation system is required for commercial cooking equipment. Information may be obtained by writing to the National Fire Protection Association, 1 Batterymarch Park, Quincy, MA 02269, www.NFPA.org. When writing, refer to NFPA No. 96.
- These units are manufactured for installation in accordance with ANSZ223.1A (latest edition), National Fuel Gas Code. Copies may be obtained from The American Gas Association, 400 N Capitol St. NW, Washington, DC 20001, www.AGA.org.

Clearances:	Combustible	Non-combustible	
Rear	2"	0"	
Sides	6"	0"	

 For proper combustion, install equipment on adjustable legs or casters. On curb or platform, allow 3½" front overhang (see diagram). Leveling bolts are required for curb installation. Specify when ordering.



Model FS-HB (No Finishing Oven)

MODEL NO.	TOTAL BTU/HR. INPUT	FINISHING OVEN	WIDTH	DEPTH	OVERALL HEIGHT	APPROX. SHP. WT. (LBS./KG)
FS-HB	100,000	_	36"	381/4"	63½"	542/244
FS-HB-MR	80,000	_	36"	381/4"	63½"	542/244
FS-HB-1	100,000	28" x 10"	36"	381/4"	78½"	662/298
FS-HB-1-MR	80,000	28" x 10"	36"	381/4"	78½"	662/298

NOTE: In line with its policy to continually improve its product, Wolf Range Company reserves the right to change materials and specifications without notice.

This appliance is manufactured for commercial use only and is not intended for home use.